





The mission of the battery test center is to conduct performance, lifetime, endurance, and safety tests on cells, modules, and batteries designed for portable, mobile, and stationary energy storage systems. A great deal of effort is devoted to characterizing batteries under various operating conditions and studying their behavior in response to abuse and crash.

"In the eLaB we investigate, test, and analyze batteries and systems according to standards or by new innovative methods."

Dr. Olaf Böse, Head of Department Accumulators



ZSW Labor für Batterietechnologie

// Contact:

Dr. Olaf Böse Head of Department Accumulators

Phone: +49 731 9530-551 Email: <u>olaf.boese@zsw-bw.de</u>

Zentrum für Sonnenenergie- und Wasserstoff-Forschung Baden-Württemberg (ZSW) Lise-Meitner-Straße 24/89081 Ulm/Germany Phone: +49 731 9530-0 / Fax: +49 731 9530-599

www.zsw-bw.de





// SAFETY TESTS

Electrical

- Controlled high current load up to 1500A / -5V...20V for testing of cell strength and components
- Short circuit test equipment up to 15kA
- Overcharge and overdischarge tests in different ranges
- Cyclingout of cell specification

Thermal

- Testing of temperature stability of cells and components up to 300°C
- High temperature exposition like flammability test


Mechanical

- Breaking strength
- Crack stability of the construction and the storage system
- Quasi static crush tests for cells, modules and battery pack systems
- Nail penetration test with different nail diameter and various penetration speed
- Identification of weak construction points by vibration and mechanical shock tests

Evaluation of extreme stress situation


Investigation of the propagation effect of a failure mode through the battery system





Identification of weakly designed parts of a system







Nail penetration test





// EQUIPMENT AND INFRASTRUCTURE

Test bunker

3 specialized bunkerfor electrical, mechanic und thermal safety tests with 100m³

Electric equipment

- Battery test unit 1 x oV...7oV/25oA
- Battery test unit 2 x -5V...+20V/750A (parallel max. 1500A)
- Battery test unit 3 x -18V...+18V/150A (parallel max. 450A)
- Battery test unit 4 x -18V...+18V/150A (parallel max. 600A)
- Battery test unit 4 x 5V...150V/30A (parallel max. 120A)
- Battery test unit 1 x oV...6oV/45oV/30oA Thy
- Short circuit switching device up to 15kA measurable and various pre resistors (1.0...200mΩ)

Thermal equipment

- 2 ovenforcell size up to 300°C
- 1 temperature chamber -70 ... 180°C
- Fire table (gas, real fire test)

Mechanical equipment

- Hydraulic multi cylinder press up to around 100 tons with different impact tools
- Nail penetration, various diameters and various feed speed (0.01 mm/s ... 100 mm/s)
- Vibration and shock test machine

Video system

- 4K / 12ofps Video recording system for recording from different positions
- ActionCams for inside use for special view of sample (optional)
- High speed image recording (optional)
- Thermal video (optional)


Infrastructure

- Gas scrubbing unit for gas cleaning (treatment of the emissions)
- Overpressure protection of the bunker
- Fire extinguishing systems (CO, and water based fire extinguisher)



Safety Test Devices





Test bunker with mechanical press with 100 tons max. force and video observation





Short circuit equipment, max. current 15 kA / Oven with 200 l volume

Mechanical Shock and Vibration Test Unit



Vibration table with acceleration force of 20 kN, load up to 50 kg, possibility of thermal and electrical superposition

// Contact:

Michael Wörz Head of Abuse Testing Department Accumulators Phone: +49 731 9530-547

Email: michael.woerz@zsw-bw.de

Zentrum für Sonnenenergie- und Wasserstoff-Forschung Baden-Württemberg (ZSW) Lise-Meitner-Straße 24/89081Ulm/Germany

Phone: +49 731 9530-500 / Fax: +49 731 9530-599 / http://www.zsw-bw.de

